

Website
www.homeplus2u.com

Customer Service
consult.homeplus@gmail.com

Instagram : [HomePlus Malaysia\(@homeplussmarthome\)](https://www.instagram.com/homeplussmarthome)

Facebook : [Home+ Malaysia\(@homeplusmartliving\)](https://www.facebook.com/homeplusmartliving)

YouTube : [HomePlus Smart Home](https://www.youtube.com/HomePlus Smart Home)

HOMe+

SMART HOME
AND
SMART LOCK
PRODUCT



Contents

Company	01	Plug	43
CoSS Protocol		Smart Plug	
AI Builder		Smart Plug (EU&FR)	
Cybersecurity			
App		Lighting	45
		Light Strip	
Interaction Center	07	Cololight PLUS	
Nature (Smart Control Panel)		BLEND Light Bulb	
		Porch Wall Lamp	
		Light Bulb	
Gateway	09		
Smart Station		Curtain Controller	53
		MINS Curtain Motor Controller	
Camera	11	BLEND Curtain Controller	
Frame		Tubular Motor	
Indoor Camera		QuickLink Curtain Motor	
Outdoor Camera		Smart Curtain Motor	
LifeSmart Smart Lock	15	Smart Control	59
Smart Door Lock (Classic)		Universal Remote Controller (SPOT)	
Yale Door Lock Module		General Controller	
		HA Interface Adaptor	
Sensor	17		
CUBE Motion Sensor		Home+ Smart Locks	63
CUBE Environmental Sensor		A7H Push-pull Smart Lock	
CUBE Door/Window Sensor		M8H Push-pull Smart Lock	
Water Leak Sensor		HD19 Smart Lock	
Gas Sensor		HD1 Smart Lock	
Motion Sensor (AAA)		HS60 Smart Grill Lock	
Human Presence Sensor (Radar Detector)			
		Intruder Alarm Kit	69
Smart HVAC	25		
Smart Central Air-conditioning Gateway			
Smart Fan Coil Thermostat			
Smart Underfloor Thermostat			
Thermostatic Radiator Valve			
Switch	31		
BLEND Smart Switch			
Moonstone Switch			
Moonstone Switch 120			
Stellar Switch			
Starry Switch			
Dimmer&Motion Sensor Switch			
CUBE Clicker			
CUBE Switch Module			
Polar Switch			
Dimmer Control			

HOMET+

**Every home
to be
smart home**





Ultra Long Distance, Super Quick Speed

CoSS protocol shares multiple advantages which include better coverage, larger capacity, lower power consumption and higher security level.

800m

CoSS can achieve ultra-long distance signal transmission of 800 meters from LifeSmart smart station to other home devices.

100ms

The signal delay could be less than 100ms.

5 years


Based on CoSS, we are able to deliver the smart switch product which supports 5 years battery life with ER18505 battery.

	CoSS	ZigBee	Wi-Fi	Z-Wave
Distance	200-800m	30-100m, can cascade devices	40m	40-100m, limited cascade of devices
Power Counsumption	Low	low	High	Low
Stability	High	High	High	Low
System Capacity	High(support more than 100 devices)	High	Low	Low
Bandwidth	Low (1kbps-128kbps)	High(256kbps)	Very High (>54mbps)	Low(9.6kbps/40kbps)
Radiation	Low(work instantaneously)	Medium (work instantaneously)	High (work continuously)	Medium (work instantaneously)
Reliability	High	High	High	High

AI Builder

Create Unlimited Devices Communication Policies

AI Builder is an open and flexible computing framework which fulfills the userspersonalized requirements now and empowered by the cloud AI on a learning basis. With AI Builder, you are able to deliver multiple outputs with multiple sensor conditions and computing policies, to create any smart home communication rules as your imagination.



LifeSmart App


LifeSmart App supports all kinds of LifeSmart devices and other third-party ZigBee/Z-Wave devices. You may monitor and interact with your home anywhere and anytime through mobile, bringing comfort and efficiency of smart home management to a new level.

System function

Push notification, AI builder, Schedule timer, Global account, OTA upgrade, Local network access, Device share, Engineering mode, RSSI monitor, Device backup.



* Minimum system requirement Android 4.0, iOS 7.0



Cybersecurity


Bank Level Encryption and Security

LifeSmart puts the cybersecurity and privacy protection as the top priority since day one. We build our system and connection with bank level encryption and security, from the smart device, edge gateway, cloud service to the applications, all the links in between are encrypted and protected.

- Bank level encryption
- Z-Wave Security S2 certification
- Independent key management for every single device
- Minimum authorization management for cloud service
- All data encryption

Privacy by Default

More over, we monitor and enforce compliance to meet industry standards and security policies such as GDPR, and we actively detect and stop the advanced threats, keep it away from our customers.



Interaction Center

The all-in-one smart terminal takes protection of you and all your properties

Nature - Smart Control Panel

LS148



The all-in-one smart control panel serving as a personal butler

- 10.25" High definition touch screen
- Configurable built-in menu to meet your needs
- Customizable physical buttons to switch scenes
- Elegant anodized aluminum craft

- Voice control
- App control
- Communicates with other devices



General		Button	
Model Number	LS148	Customizable scene-switch button×4	
Installation	In-wall concealed with pre-embedded back box(standard)	Power button	
Operating Temperature	-5~45	Screen	10.25 inch touch screen
Operating Humidity	5~90%	Resolution	1920×720
Network	Wi-Fi 2.4GHz/ Ethernet	CPU	4 Core ARM
Power Consumption	<20W	Power Supply	AC 100-240V 50/60Hz
Interface	Live/Neutral/Earth wire in	RAM	2GB
	Ethernet RJ45	Operating System	Android 5.1
	HDMI in	Bluetooth	Yes (Bluetooth 4.2)
	USB	Speaker	Yes
		Microphone	Yes

Construction	
Color	Matte grey
Dimensions	Exposed dimension: 342*122*16mm Backbox dimension: 335*114*70mm
Weight	1260g(panel only)
Casing	Aircraft aluminum

Nature 7

Best light luxury smart panel



- 7" High definition touch screen
- Mainstream wireless protocol all in one
- 4 Physical keys for numerous scenarios
- Elegant anodized aluminum craft

Voice control App control Communicates with other devices



Nature Mini

Integrating all physical switches in one screen,



- 4" High definition touch screen
- Integrated with IoT gateway and smart switch
- Set and enable kinds of scenarios through this switch panel
- Control music, lighting, curtain, HVAC and others

Voice control App control Communicates with other devices



General

Model Number	LS226WH- LS228WH
Installation	In-wall concealed with 86 back box(standard)
Operating Temperature	-5~45
Operating Humidity	5~90%
Network	Wi-Fi 2.4GHz/ Ethernet
Power Consumption	<20W
Interface	Live/Neutral Light1 Light2 Light3 wire in

Button	Customizable scene-switch
Screen	4" inch touch screen
Resolution	480 x 480
CPU	4 Core ARM
Power Supply	AC 100-240V 50/60Hz
RAM	2GB
Operating System	Linux
Bluetooth	Yes (Bluetooth 4.2)
Speaker	Yes
Microphone	Yes

Construction

Color	White/ Black
Dimensions	Outside dimension: 86*86*11mm Whole product dimension: 86*86*36mm
Weight	90g(panel only)
Casing	Flameresistant PC

Gateway

More than convenient when everything gets connected



Smart Station


LS082WH LS090WH (Japan)

Center of the smart home ecosystem and make all the devices work seamlessly

- Powerful processor with up to 500 connected devices
- 800m wireless signal distance
- AI builder for automated processing
- Multiple-protocol support



- Voice control
- App control
- Communicates with other devices



Radio	Smart Station	Smart Station (CoSS+Zigbee)	Smart Station (CoSS+Z-Wave)
Radio Protocol	CoSS	CoSS & Zigbee	CoSS & Z-Wave
Radio Frequency	433~922MHz	CoSS: 433~922MHz / Zigbee: 2.4GHz	CoSS: 433~922MHz / Z-Wave
Signal Distance (Open Field)	800m	CoSS: 800m / Zigbee: 30-100m	CoSS: 800m / Zigbee: 40-100m





General	
Model Number	LS082WH
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 5V
Power Consumption	<2.5W
Interfaces	Power supply / RJ45 / Reset hole
Indicator	Yes
Connected Devices	500
Network	LAN(10/100/1000 BASE-T via RJ45 port)

Construction	
Color	Ivory white
Dimensions	110.8*110.8*28mm
Weight	120g
Casing	ABS

Indoor Camera

LS198

An intelligent indoor camera with human detection, allowing you to monitor what matters, without receiving annoying false alerts

-  1080P high definition real-time monitoring
-  Two-way talk
-  IR night view
-  Moving human detection and alarm notifications

 Voice control  App control



General	
Model Number	LS198
Fov	90°
Operating Temperature	-20°~60°
Operating Humidity	5~90%
Power Supply	DC 5V
Power Consumption	<5W
Battery	No
Interface	Micro USB power input TF card slot
Indicator	No
Ingress Protection	Indoor
Communication protocol	Wi-Fi 2.4GHz
Button	Pairing/operating button
Resolution	1080P
Compression	H.264
Night View	IR 8m
PTZ	Horizontal 355° remote panning Vertical 89° remote tilting
Motion Alarm	Yes

Audio	
Two-way Talk	Yes
Audio Message	No
Speaker	Yes
Mic	Yes





Storage	
Built-in Storage	No
External Storage	TF card

Construction	
Color	Ivory white
Dimension	78.5*78.5*115mm
Weight	180g
Casing	ABS

Outdoor Camera

LS179

1080P outdoor camera with sound-light alarm to actively guard your house 24/7

-  1080P high definition real-time monitoring
-  Active deterrence with sound-light alarm
-  IR night view
-  IP66 ingress protection for outdoor installation

 Voice control  App control  Communicates with other devices



General	
Model Number	LS179
Fov	110°
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 12V
Power Consumption	<12W
Battery	No
Interface	Power port Ethernet port Antenna port TF card slot
Indicator	No
Ingress Protection	Indoor/Outdoor IP66
Communication protocol	Wi-Fi 2.4GHz
Button	Pair/operate button
Resolution	1080P
Compression	H.264
Night View	IR 10m
PTZ	Manual adjustment

Audio	
Two-way Talk	Yes
Audio Message	No
Speaker	Yes
Mic	Yes

Storage	
Built-in Storage	No
External Storage	TF card

Construction	
Color	Ivory white
Dimension	66*66*182mm(with bracket)
Weight	375g
Casing	Aluminium alloy casing

Smart Door Lock Classic

LS101GS/SL

A smart lock with multiple ways for access and can communicate with your home devices

- Multiple access
- Anti-theft lock case
- Detect break-in and entrance attempts

- Voice control
- App control
- Communicates with other devices



General

Model Number	LS101GS/SL
Color	Gold / Silver
Dimensions	385*75*33mm
Weight	4130g
Casing	Glass panel, zinc alloy
Lock Case Grade	Super-B anti-theft lock case
Compatible Lock	6068 lock body
Lock Body Size	24*240 Square lock body (standard) 30*240 Round lock body (optional) 388 series overlord lock (optional)
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening
Unlock Mode	Fingerprint, password, NFC card, emergency key
Fingerprint Module	Biological fingerprint sensor
Rejection Rate	1%
False Recognition Rate	0.001%
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password Privacy guard password Hijacking password alarm
Storage Quantity	Fingerprint*100/ Password*30/ NFC card*255

Operating Temperature	-30~60
Operating Humidity	20~90%
Power Supply	8 AA alkaline batteries, 12V
Emergency Power Supply	USB
Battery Life	10 times per day, last about 1 year
Interface	Micro USB emergency power interface
Button	Fingerprint button Keyboard Reset button Code matching button Doorbell button Door lock safety knob Back cover open button
Display	LED display
Camera	N/A
Speaker	High fidelity speaker
Microphone	HD microphone

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	CoSS: 200m



SMART DOOR LOCK

Sensors

Stable operation, stay connected

CUBE Motion Sensor

LS062WH LS150WH (Japan)

A tiny Motion sensor combined PIR technology and light detection



120° wide angle detection



Built-in light sensor to switch day/night mode



Notifications and record searching via the app



Compact size and could be placed anywhere



Voice control



App control



Communicates with other devices



General	
Model Number	LS062WH / LS150WH (Japan)
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	1 Battery CR2450, 3V
Static Consumption	<1mW
Battery Life	Up to 1 year
Sensitive Element	Passive infrared sensor, light sensor
Detection	5m/120°
Interface	-
Button	-
Indicator	LED
Display	-
Audio	-

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	100m

Construction	
Color	Ivory white
Dimensions	38.4*38.4*22.4mm
Weight	20 g
Casing	ABS+PC



CUBE Environmental Sensor

LS063WH LS091WH (Japan)

One device to simultaneously monitor the temperature, humidity and illumination and indicate these data with a LCD display



Built-in multiple sensors including temperature detection, humidity detection and light detection



Real-time data display on the screen



Notifications and record searching via the app



Tiny size and could be placed anywhere



Voice control App control Communicates with other devices



General	
Model Number	LS063WH / LS091WH (Japan)
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	1 Battery CR2450, 3V
Static Consumption	<1mW
Battery Life	Up to 1 year
Sensitive Element	Temperature sensor, humidity sensor, light sensor
Detection	Temperature, humidity, light
Interface	-
Button	Pairing button
Indicator	LED
Display	LCD
Audio	-

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	100m

Construction	
Color	Ivory white
Dimensions	38.4*38.4*16.2mm
Weight	24g
Casing	ABS+PC

CUBE Door/Window Sensor

LS058WH LS149WH (Japan)

A simple-to-install door/window sensor combined magnetic sensor and vibrating sensor



Remote alarm once opening or vibrating detected



Real-time feedback on door/window status



Notifications and record searching via the app



One-button for scenes control



Voice control App control Communicates with other devices



General	
Model Number	LS058WH / LS149WH (Japan)
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	1 Battery CR2450, 3V
Static Consumption	<1mW
Battery Life	Up to 1 year
Sensitive Element	Magnetic sensor, vibration sensor
Detection	Slide and shake detection of the door and window
Interface	-
Button	Customizable button, pairing button
Indicator	LED
Display	-
Audio	-

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	100m

Construction	
Color	Ivory white
Dimensions	38.4*38.4*14.6mm
Weight	20g
Casing	ABS+PC

Switches

Siri-controlled switches free your hands



BLEND Smart Switch

LS055WH/GD/BL LS056WH/GD/BL LS057WH/GD/BL

Replace your traditional switch to the smart one and make the lights freely controlled



Simple modern design



Customized 16 million colors panel light



Dual control, multiple control




Voice control



App control



Communicates with other devices



General

Wiring	Live+neutral
Control Unit	16A magnetic latching relay
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<1.5W
Maximum Overload	Resistive load: 500W per channel Inductive/Capacitive load: 200W per channel
Indicator	16Million colors, brightness adjusted

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

BLEND Light Switch (1 way)

Model Number	LS055WH/GD/BL
Weight	100g

BLEND Light Switch (2 way)

Model Number	LS056WH/GD/BL
Weight	110g

BLEND Light Switch (3 way)

Model Number	LS057WH/GD/BL
Weight	120g





Construction

Color	White / Black / Golden
Dimension	86*86*36.5mm
Casing	ABS+PC

Moonstone Switch


LS139WH/BL LS140WH/BL LS141WH/BL

Touchable switch leads you into a simple smart life

-  Simple modern design, jade like touch
-  Vibration interactions
-  Customized 16 million colors indicator light
-  Dual control, multiple control



 Voice control  App control  Communicates with other devices



General	
Wiring	Live+neutral
Control Unit	16A magnetic latching relay
Operating Temperature	5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<1.5W
Maximum Overload	Resistive load: 500W per channel Inductive/Capacitive load: 200W per channel
Indicator	16Million colors

Construction	
Color	White glass+Golden frame/ White glass+White frame/ Black glass+Golden frame
Dimension	86*86*36mm
Casing	Bottom cover: PC, top cover: ABS+PC, front panel: glass

Moonstone Switch (1 way)	
Model Number	LS139WH/BL
Weight	136g

Moonstone Switch (1 way)	
Model Number	LS140WH/BL
Weight	141g





Moonstone Switch (1 way)	
Model Number	LS141WH/BL
Weight	148g

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	200m

Moonstone Switch 120


LS139WH/BL LS140WH/BL LS141WH/BL

Touchable switch leads you into a simple smart life

-  Simple modern design, jade like touch
-  Vibration interactions
-  Customized 16 million colors indicator light
-  Dual control, multiple control



 Voice control  App control  Communicates with other devices



General	
Wiring	Live+neutral
Control Unit	16A magnetic latching relay
Operating Temperature	5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<1.5W
Maximum Overload	Resistive load: 500W per channel Inductive/Capacitive load: 200W per channel
Indicator	16Million colors

Construction	
Color	White glass+White frame/ Black glass+White frame
Dimension	120*72*35mm
Casing	Bottom cover: PC, top cover: ABS+PC, front panel: glass

Moonstone Switch 120 (1 way)	
Model Number	LS123WH/BL
Weight	151g

Moonstone Switch 120 (1 way)	
Model Number	LS124WH/BL
Weight	158g





Moonstone Switch 120 (1 way)	
Model Number	LS125WH/BL
Weight	167g

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	200m


Stellar Switch

LS170WH/GD LS171WH/GD LS172WH/GD LS173WH/GD

Independent power supply, perfect solution for live only wiring

-  Human engineering design for comfortable touch
-  No flicker, safe and stable
-  No need to damage your wall for extra wiring
-  Dual control, multiple control

 Voice control  App control  Communicates with other



General

Control Unit	16A magnetic latching relay
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 5V-30V Or AC 90-250V
Static Consumption	<1mW
Maximum Overload	Resistive load: 500W per channel Inductive/Capacitive load: 200W per channel DC load: 30V/5A
Battery Type	ER18505M(substitute: CR17505 or ER17505)
Battery Life	5 years

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

Construction

Color	White / Golden
Dimension	86*86*39mm
Casing	ABS+PC

Stellar Switch (1 way)

Model Number	LS170WH/GD
Wiring	Live only / Live+neutral
Weight	115g

Stellar Switch (2 way)

Model Number	LS171WH/GD
Wiring	Live only / Live+neutral
Weight	124g

Stellar Switch (3 way)

Model Number	LS172WH/GD
Wiring	Live only / Live+neutral
Weight	133g





Dual Control Only

Model Number	LS173WH/GD
Wiring	No wiring
Weight	99g

Starry Switch

LS185WH/BL/GD LS186WH/BL/GD LS187WH/BL/GD

Independent power supply, perfect solution for live only wiring

-  Human engineering design for comfortable touching
-  No flicker, safe and stable
-  No need of external wiring
-  Dual control, multiple control

 Voice control  App control  Communicates with other devices



General

Control Unit	16A magnetic latching relay
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 5V-30V Or AC 90-250V
Static Consumption	<1mW
Maximum Overload	Resistive load: 500W per channel Inductive/Capacitive load: 200W per channel DC load: 30V/5A
Battery Type	ER18505M(substitute: CR17505 or ER17505)
Battery Life	5 years

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

Construction

Color	White / Black / Golden
Dimension	86*86*39mm
Casing	ABS+PC

Starry Switch (1 way)

Model Number	LS185WH/BL/GD
Wiring	Live only / Live+neutral
Weight	126g

Starry Switch (2 way)

Model Number	LS186WH/BL/GD
Wiring	Live only / Live+neutral
Weight	135g

Starry Switch (3 way)

Model Number	LS187WH/BL/GD
Wiring	Live only / Live+neutral
Weight	144g

Dual Control Only


Model Number	LS188WH/BL/GD
Wiring	No wiring
Weight	110g





Dimmer & Motion Sensor Switch

LS174 LS154 (Japan)

Customize your own brightness with motion detection

 Multiple ways of lighting adjustment

 Automatically switch on and off by human motion detection

 Precise brightness control by percentage

 Voice control  App control  Communicates with other devices



General	
Product Type	Wall mount switch
Wiring	Live+neutral
Control Unit	Triac control unit(one way)
Compatible Lights	Filament, halogen, LED lamp or other lamp with triac control
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<1W
Maximum Overload	Resistive load: 250W Inductive/Capacitive load: 200W
Button	Dimmer button (Pressable) pairing&matching button Safety button
Indicator	Dimmer indicator light
Motion Detection	Yes (embedded motion sensor)
Light Detection	Yes (embedded light sensor)

Dimmer&Motion Sensor Switch (CoSS)	
Model Number	LS174 / LS154 (Japan)
Radio Protocol	CoSS
Radio	
Signal Range (Open Field)	100m
Construction	
Color	Ivory white
Dimension	120*70*47mm (with dimmer button) 68*40*27mm (flush-mount)
Weight	110g
Casing	Bottom cover: PC, others: ABS+PC



CUBE Clicker

LS069WH/RD/WG LS151WH (Japan)

A simple click to run complex scenes



Compact size and could be placed anywhere



Easily switch to different scenes



Multiple color options (White/Red/Wood)



Voice control



App control



Communicates with other devices

General

Model Number	LS069WH/RD/WG / LS151WH (Japan)
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	1 Battery CR2450, 3V
Battery Life	Up to 1 year
Button	Control button pairing button
Indicator	LED

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	100m

Construction




Color	White / Red / Wood
Size	38.4*38.4*14.6mm
Weight	20g
Casing	ABS+PC




UK Plug

LS002

Smart remote control, changing traditional electronic appliances to be smart ones

-  Easy pairing
-  Scheduled task
-  Secure casing with flameresistant material

-  Voice control
-  App control
-  Communicates with other devices



General

Model Number	LS002
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<0.5W
Maximum Overload	10A
Button	Pairing/operating button
Indicator	Brightness adjustable LED
Electricity Metering	No
Manual Control	Yes
Installation	Plug and play
Socket Standard	New national standard 2/3 holes mutual socket

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

Construction

Color	Ivory white
Dimension	65*65*36mm
Weight	95g
Casing	Flameresistant PC



Lightings

Dim the lights without
lifting a finger



Light Strip

LS065

A perfect 16 million colors lighting strip with adjustable brightness and preset modes to provide different atmospheres



Low power LED technology



16 Million colors to create various lighting effects



Brightness adjustment



Voice control



App control



Communicates with other devices



General

Model Number	LS065
Lighting Color	16 million colors + white
Lamp Model	-
Luminous Flux	360lm
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 24V
Power Consumption	<12W/m

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

Construction

Color	-
Dimensions	2000*12*3.5mm
Weight	Light strip weight :114g/2meters

Cololight PLUS

Design your own style and treat yourself with a unique lighting experience



Create your own design with the modular light panels



16 Million colors to create various lighting effects



A music visualizer-Cololight syncs with your music



Infinite splicing without limitation



Construction	Cololight PLUS (HomeKit Set)	Cololight PRO (Starter Set)	Cololight PRO (Stone Set)
Model Number	LS167	LS166A3	LS166A6
Model Content	Homekit main controller Cololight Connector Fixator	Main controller*1 Cololight*3 Plastic base*1 Connector*3	Main controller *1 Cololight *6 Stone base *1 Connector *6 Fixator *4
Housing Color		Ivory white	
Module Size	Led module :86*74.5*30.5mm Homekit controller :46.5*30.5*28mm Fixator :16.5*17.5*9mm Connector :23.1*17.5*9mm	Led module :86*74.5*30.5mm Controller :73.1*45*8.9mm Plastic base :168.2*63.1*23mm Fixator :16.5*17.5*9mm Connector :23.1*17.5*9mm	Led module :86*74.5*30.5mm Controller :73.1*45*8.9mm Stone base :86*86*61mm Fixator :16.5*17.5*9mm Connector :23.1*17.5*9mm
Weight	Led module :52.5g Homekit controller :54g Fixator :2g Connector :2.6g	Led module :52.5g Controller :30g Plastic base :35.5g Fixator :2g Connector :2.6g	Led module :52.5g Controller :30g Stone base :550g Fixator :2g Connector :2.6g
Casing		Upper cover: ABS; others: ABS+PC	


General	
Led Color	16 Million color
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 5V 2A (each 10 light units require 1 ampere extra power)
Power Consumption	0.3W at lowest, max. <5W
Maximal Connecting Led Module	Up to 255 units per controller
Radio Protocol	Wi-Fi 2.4GHz
Touch Button	Yes, on the main controller
Number of LEDs Per Module	19 Led lights in one Cololight module, can be individually controlled
Features	app control, touch button control, bluetooth pairing, timer function, group control, play library for multiple effects


Cololight (Extension)	
Model Number	LS161
Model Content	Cololight Connector


BLEND Light Bulb -

E27 ^{LS024}

A perfect 16 million colors lighting bulb with adjustable brightness and preset modes for lighting up your home


 Low power LED technology




 16 Million colors to create various lighting effects

 Brightness adjustment

 Good design with capsule casing




 Voice control  App control  Communicates with other devices

 Works with Apple HomeKit  works with the Google Assistant  WORKS WITH amazon alexa

General	
Model Number	LS024
Lighting Color	16 million colors + white
Lamp Model	E27
Luminous Flux	220lm
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Power Consumption	Static consumption < 0.5W Nominal consumption 2W (RGB 3W, white 3W)

Construction	
Color	Silver
Dimensions	50*110mm
Weight	78g
Casing	Aluminum alloy

Radio	
Radio Protocol	CoSS
Signal Range (Open Field)	200m



Curtain Controllers
Embrace the morning
sunshine while lying in bed

MINS Curtain Motor Controller

LS178

Turn your traditional curtain motor into a smart one



No need to damage your wall for extra wiring



Upgrade the motors of garage door easily



Scheduled task



Accurate control by percentage



Voice control



App control



Communicates with other devices



General

Model Number	LS178
Control Unit	Relay: 2A magnetic latching
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 3V
Static Consumption	< 1mW
Battery Model	2 AA Batteries
Interface	RJ11 input RJ11 output 10 Pin input 10 Pin output

Construction

Color	Ivory white
Dimensions	135*32*23mm
Weight	55g (excluding battery)
Casing	ABS+PC





Radio

Radio Protocol	CoSS
Signal Range (Open Field)	100m

BLEND Curtain Controller

LS074WH
LS074GD
LS074BL

A good design panel for curtains' easy control

-  Simple Modern Design
-  One tap to control the whole shading system
-  Scheduled task
-  Accurate control by percentage



 Voice control  App control  Communicates with other devices



General

Model Number	LS074WH / LS074GD / LS074BL
Wiring	Live+neutral
Control Unit	16A magnetic latching relay
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	AC 100-240V 50/60Hz
Static Consumption	<1.5W
Maximum Overload	Max. 500W
Indicator	16 million colors
Interface	Neutral wire input Live wire input Opening signal input Closing signal input

Construction

Color	White / Golden / Black
Dimensions	86*86*36.5mm
Weight	110g
Casing	ABS+PC





Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

Tubular Motor

WSER40Q-8/23 WSER40Q-8/19

Integrate the roller blinds into your smart home system

-  Quiet motor with operating sound below 40dB
-  One tap to control the whole shading system
-  Scheduled task support
-  Accurate control by percentage

 Voice control  App control  Communicates with other devices



 Works with Apple HomeKit  works with the Google Assistant  WORKS WITH amazon alexa

General

Wiring	Live+neutral+ground
Rated Torque	8 N.m
Running Time	4 min
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Cable Length	125cm
Button	Pair button
Indicator	-
Ingress Protection	IP44
Strong Power	Yes
Weak Power	Yes
Receiver Control	Yes
Electronic Limit Swtich	Yes
Manual Contraol	Yes
3rd Intermediate Limit Position	Yes
Obstacle Stop Function	Yes
Hand Operable During Power-o	Yes
Auto End Limits Setting	Yes
Maximal Track Length	2.5m
Maximal Load	10Kg

WSER40Q-8/23

Output Speed	23 rpm
Power Supply	AC 120V, 0.88A
Power Consumption	103W

WSER40Q-8/19

Output Speed	19 rpm
Power Supply	AC 230V, 0.53A
Power Consumption	121W

Construction

Color	White
Dimensions	39*555mm
Weight	1.34Kg
Casing	Steel





Radio

Radio Protocol	CoSS
Signal Range (Open Field)	200m

QuickLink Curtain Motor

BCM100D

Turn your traditional curtains into smart ones

-  Adjustable track length
-  One tap to control the whole shading system
-  Scheduled task
-  Accurate control by percentage



 Voice control  App control  Communicates with other devices



General

Model Number	BCM100D
Curtain Track Length	Maximal 5.2m
Moving Speed	12cm/s
Rated Torque	1.2Nm
Operating Temperature	-20~85
Operating Humidity	0~80%
Power Supply	100-240V AC 50/60Hz
Power Consumption	40W
Power Cable Length	85cm
Interface	RJ11
Button	Coding / Setting button
Track Set	Track(1m)* 4, track (0.5m), track(0.2m)*2, track(0.1m), connector(0.2m), connector(0.1m)*5

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	100m

Maximal Load	40Kg
Indicator	LED
Ingress Protection	IP20
Strong Power	Yes
Weak Power	Yes
Receiver Control	Yes
Electronic Limit Swtich	Yes
Manual Contraol	Yes
3rd Intermediate Limit Position	Yes
Obstacle Stop Function	Yes
Hand Operable During Power-o	Yes
Auto End Limits Setting	-




Construction

Color	White
Dimensions	270*50*50mm
Weight	5kg
Casing	ABS, aluminum




Smart Curtain Motor


LS133WH

Turn your traditional curtains into smart ones

-  One tap to control the whole shading system
-  Scheduled task
-  Accurate control by percentage



 Voice control  App control  Communicates with other devices



General

Model Number	LS133WH
Moving Speed	14cm/s
Rated Torque	1.2Nm
Operating Temperature	-5~45
Operating Humidity	5~90%
Ingress Protection	IP40
Power Supply	AC 100V-240V 50/60Hz
Power Consumption	13W
Power Cable Length	125cm
Interface	Serial port Weak urrent switch interface
Indicator	LED
Maximal Track Length	8m
Maximal Load	50Kg

Radio

Radio Protocol	CoSS
Signal Range (Open Field)	100m

Button	Reset/Receiver pairing button Smart station pairing button
Ingress Protection	IP40
Strong Power	Yes
Weak Power	Yes
Receiver Control	Yes
Electronic Limit Swtich	Yes
Manual Contraol	Yes
3rd Intermediate Limit Position	Yes
Obstacle Stop Function	Yes
Hand Operable During Power-o	Yes
Auto End Limits Setting	Yes

Construction





Color	White
Dimensions	365*60*50mm
Weight	1.3KG
Casing	Aircraft aluminum

Smart Controls
The brains empower deep
integration

Universal Remote Controller - SPOT

LS034SL
LS136
LS152 (Japan)

A fantastic IR remote controller to simplify your life by interacting with all LifeSmart product series

-  Universal IR remote control
-  Unique exterior design - ornamental and also practical as a desktop storage unit
-  Convenient USB charge interface
-  16 Million colors to create various lighting effects

-  Voice control
-  App control
-  Communicates with other devices



General	
Operating Temperature	-5~45
Operating Humidity	5~90%
Power Supply	DC 5V
Interfaces	Micro USB power supply USB output
Button	Configuration button
Indicator	16 million color
Remote Range	360°, 5-10m
Remote Frequency	38KHz

Software	
APP Control	Yes
Voice Control	Yes
Code Library Match	Yes
Code Library Update	Yes
Remote Control Learning	Yes

SPOT (WiFi Series)	
Model Number	LS136(CoSS)
Power Consumption	1.3W
Radio Protocol	Wi-Fi 2.4GHz
Signal Range (Open Field)	50m




SPOT (CoSS Series)	
Model Number	LS136 / LS152(Japan)
Power Consumption	1W
Radio Protocol	CoSS
Signal Range (Open Field)	100m

Construction	
Color	Ivory white
Dimensions	128*128*53mm
Weight	260g
Casing	ABS

Smart Locks
 Convenience
 Security
 Life Style

A7H Push-pull Smart Lock

A smart lock with multiple way to access and can communicate with Tuya smart home devices

-  **Multiple access**
-  **Anti-theft lock case**
-  **Detect break-in and entrance attempts**

-  Door bell
-  App control
-  Communicates with other devices



General	
Model Number	A7H
Color	Black
Material	Zinc Alloy
Compatible Lock	6068 lock body
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening/
Unlock Mode	Fingerprint, Password, NFC card, Mobile App, Emergency key
Storage Quantity	Fingerprint*100/ Password*100/ NFC card*100
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password
	One-key protection
Operating Temperature	-20~60°C
Operating Humidity	15%~93%
Power Supply	4~8AA alkaline batteries, 5V
Emergency Power Supply	USB




Radio	
Radio Protocol	BLE, WiFi with gateway
Range (Open Field)	5~10m

Construction	
Color	Black
Dimensions	420*69*55mm (Front) 420*69*57mm (Back)
Weight	6.5kg



M8H Push-pull Smart Lock

A smart lock with multiple way to access and can communicate with Tuya smart home devices

-  Multiple access
-  Anti-theft lock case
-  Detect break-in and entrance attempts

-  Door bell
-  App control
-  Communicates with other devices



General

Model Number	M8H
Color	Black
Material	Zinc Alloy
Compatible Lock	6068 lock body
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening
Unlock Mode	Fingerprint, Password, NFC card, Mobile App, Emergency key
Storage Quantity	Fingerprint*100/ Password*100/ NFC card*100
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password
	Remote Unlock
Operating Temperature	-20~60°C
Operating Humidity	15%~93%
Power Supply	7.4V lithium battery
Emergency Power Supply	USB

Radio




Radio Protocol	WiFi
Range (Open Field)	10m

Construction

Color	Black
Dimensions	420*76*65mm (Front) 420*76*75mm (Back)
Weight	4.7kg

HD19 Smart Lock

A smart lock with multiple way to access and can communicate with Tuya smart home devices

-  Multiple access
-  Anti-theft lock case
-  Detect break-in and entrance attempts

-  Door bell
-  App control
-  Communicates with other devices



General

Model Number	HD19
Color	Black
Material	Zinc Alloy
Compatible Lock	6068 lock body
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening
Unlock Mode	Fingerprint, Password, NFC card, Mobile App, Emergency key
Storage Quantity	Fingerprint*100/ Password*100/ NFC card*100
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password
	Remote Unlock
Operating Temperature	-20~60°C
Operating Humidity	15%~93%
Power Supply	4AA alkaline batteries, 5V
Emergency Power Supply	USB

Radio




Radio Protocol	WiFi
Range (Open Field)	10m

Construction

Color	Black
Dimensions	358*70*82mm (Front) 358*70*82mm (Back)
Weight	4.5kg

HD1 Smart Lock

A smart lock with multiple way to access and can communicate with Tuya smart home devices

-  Multiple access
-  Anti-theft lock case
-  Detect break-in and entrance attempts

-  Alarm
-  App control
-  Communicates with other devices






General	
Model Number	HD1
Color	Black
Material	Zinc Alloy
Compatible Lock	6068 lock body
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening
Unlock Mode	Fingerprint, Password, NFC card, Mobile App, Emergency key
Storage Quantity	Fingerprint*100/ Password*100/ NFC card*100
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password
	Remote Unlock
Operating Temperature	-20~60°C
Operating Humidity	15%~93%
Power Supply	4AA alkaline batteries, 5V
Emergency Power Supply	USB

Radio	
Radio Protocol	WiFi / BLE
Range (Open Field)	10m

Construction	
Color	Black
Dimensions	370*75*72mm (Front) 370*75*72mm (Back)
Weight	4kg

HS60 Smart Grill Lock

A smart lock with multiple way to access and connected with TLock

-  Multiple access
-  Prevent unauthorized exit
-  Double fingerprint

-  Double lock
-  App control
-  Communicates with TLock



General	
Model Number	HS60
Color	Black
Material	SUS304 Stainless Steel
Compatible Lock	2885 lock body
Open Direction	Left outer opening/ Right outer opening/ Left inner opening/ Right inner opening
Unlock Mode	Fingerprint, Password, NFC card, Mobile App, Emergency key
Storage Quantity	Fingerprint*100/ Password*100/ NFC card*100
Password Length	6-12 Digit
Cryptographic Function	Visitor temporary password
	Remote Unlock
Operating Temperature	-20~60°C
Operating Humidity	15%~93%
Power Supply	4AAA alkaline batteries, 5V
Emergency Power Supply	USB

Radio	
Radio Protocol	BLE
Range (Open Field)	5~10m

Construction	
Color	Black
Dimensions	300*40*25mm (Front) 300*40*25mm (Back)
Weight	3kg

INTRUDER ALARM KIT

Defend your home

- Tamper prevention for all devices
- GSM alarm message
- Power-off prevention
- Compatible with third-party cameras
- Communicates with other smart home devices



OPEN
RESPECT
EXCELLENCE
DELIVER



KL

A-02-23, Plaza Bukit Jalil (Aurora Place), No. 1, Persiaran Jalil 1, Bandar Bukit Jalil, 57000 Kuala Lumpur